

Obduramus Circum-FLEX

Flexible Internal repair sleeve

Item number	Sleeve DN mm	Sleeve length mm	Total Ø rolled mm	Max radial offset mm	Max angular deviations °	V4A stainless steel sleeve			EPDM seal			Designed for pipes:		Individual Sealing length mm
						Sheet thickness mm	Roll size mm	Max. expansion mm	Rubber thickness mm	Sealing lips height mm	Height incl. lips mm	Min internal Ø mm	Max internal Ø mm	
A-1-150 Flex	150	400	129	20	5	1,0	117	154	2,0	5,0	7,0	140	162	310
A-1-200 Flex	200	400	164	20	5	1,2	150	204	2,0	5,0	7,0	175	215	310
A-1-225 Flex	225	400	180	20	5	1,2	165	222	2,0	5,0	7,0	190	232	310
A-1-250 Flex	250	420	202	20	5	1,2	190	254	2,0	5,0	7,0	215	262	330
A-1-300 Flex	300	420	251	20	5	1,2	235	306	2,0	6,0	8,0	262	316	330
A-1-375 Flex	375	420	310	20	5	1,2	290	390	2,0	8,0	10,0	320	398	330
A-1-400 Flex	400	420	345	20	5	1,5	325	407	2,0	8,0	10,0	355	420	330
A-1-450 Flex	450	450	382	20	5	1,5	360	460	2,5	8,0	11,0	400	468	350
A-1-500 Flex	500	450	442	20	5	1,5	420	506	2,5	8,0	11,0	451	520	350
A-1-525 Flex	525	450	442	20	5	1,5	420	530	2,5	8,0	11,0	455	538	350
A-1-600 Flex	600	450	531	20	5	2,0	510	610	2,5	8,0	11,0	541	623	350

All sleeves both ends flared.

Incl. backing foil made of PE thickness 1mm

Dimensions within the scope of our production tolerances.