

Obduramus Circum-MINI

Internal repair sleeve

Item number	Sleeve DN	Sleeve length	Total Ø rolled	V4A stainless steel sleeve			EPDM seal			Designed for pipes:		Individual Sealing length	Total weight
				Sheet thickness	Roll size	Max. expansion	Rubber thickness	Sealing lips height	Height incl. lips	Min. internal Ø	Max. internal Ø		
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
1-150 Mini*	150	400	129	1,0	117	154	2,0	5,0	7,0	140	162	310	2,1
1-175 Mini	175	400	147	1,0	133	182	2,0	5,0	7,0	157	188	310	2,5
1-200 Mini	200	400	164	1,2	150	204	2,0	5,0	7,0	175	215	310	3,1
1-225 Mini	225	400	180	1,2	165	222	2,0	5,0	7,0	190	232	310	3,6
1-250 Mini	250	420	202	1,2	190	254	2,0	5,0	7,0	215	262	330	4,1
1-300 Mini	300	420	251	1,2	235	306	2,0	6,0	8,0	262	316	330	4,8
1-375 Mini	375	420	310	1,2	290	390	2,0	8,0	10,0	320	398	330	6,0
1-400 Mini	400	420	345	1,5	325	407	2,0	8,0	10,0	355	420	330	7,7
1-450 Mini	450	450	382	1,5	360	460	2,5	8,0	11,0	400	468	350	9,4
1-500 Mini	500	450	442	1,5	420	506	2,5	8,0	11,0	451	520	350	10,6
1-525 Mini	525	450	442	1,5	420	530	2,5	8,0	11,0	455	538	350	
1-600 Mini	600	450	531	2,0	510	610	2,5	8,0	11,0	541	623	350	16,5
1-700 Mini	700	450	621	2,0	600	714	2,5	8,0	11,0	631	727	350	19,6
1-750 Mini	750	450	612	2,0	590	760	2,5	8,0	11,0	635	768	350	
1-800 Mini	800	450	721	2,0	700	810	2,5	8,0	11,0	731	823	350	22

All sleeves are available without flaring, with one-end flared or both ends flared. Please specify when ordering..

Dimensions within the scope of our production tolerances..

*Serial installation of DN 150 is possible in stoneware with 2 sleeves..